

Filling, sounding and de-aeration system				Top Part	M351
Project No.	513233	Function	351	Drawn	NCO
Yard No.	Section/Compartment			Check	CPAD01
COPYRIGHT DAMEN SHIPYARDS GROUP				Document number	5497690
				Date	09-11-2023
				Sheet	1
				Revision	A01

POS	PART		DESCRIPTION	DOC NO
	QT.	UNITS		
001	1010669		[TA], ASSY, De-aerator, Type 1 WIN2000 High Inlet Air Speed (HIAS),	1079674
	2	pcs	DN200, Flange, PN10, Closable, Aluminium, Epoxy painted, Mounting	1
002	1185833		Check valve, 2630D, Floating ball, Straight, DN65, Flange, Sealing:NBR	
	1	pcs	, PN16, FL:PN10, Cast iron GGG 40 (EN-JS 1030), Coated, EN 558-1	
003	1000323		Check valve, 2630D, Floating ball, Straight, DN80, Flange, Sealing:NBR	
	2	pcs	, PN16, FL:PN10, Cast iron GGG 40 (EN-JS 1030), Coated, EN 558-1	
004	1010634		[TA], ASSY, De-aerator, Type 1 WIN2000 High Inlet Air Speed (HIAS),	
	4	pcs	DN65, Small flange, PN10, Aluminium, Epoxy painted, Flame arresto	
005	1039178		ASSY, Pipe, With Cap, Assembly with cap and chain, DN40, Stainless	1239307
	5	pcs	steel	1
006	1002167		[TA], ASSY, De-aerator, Type 1 WIN2000 High Inlet Air Speed (HIAS),	1079674
	4	pcs	DN50, Small flange, PN10, Aluminium, Epoxy painted, Flame arresto	1
007	1010635		[TA], ASSY, De-aerator, Type 1 WIN2000 High Inlet Air Speed (HIAS),	1079674
	1	pcs	DN80, Small flange, PN10, Aluminium, Epoxy painted, Flame arresto	1
009	1012273		S.C. Flange: Fuel oil, DN65, PN10, OD=220mm, di=77.3mm, t=20mm,	1246358
	1	pcs	PCD=145mm, n=8x, 22mm, St st AISI 316L (1.4404)	1
010	1245442		S.C. Flange: Fuel oil blind, PN10, OD=220mm, t=20mm, PCD=145mm, n=8x,	1649875
	1	pcs	22mm, St st AISI 316L (1.4404), DN40-DN80	1
011	1012252		S.C. Flange: Sanitary discharge, DN65, PN10, OD=210mm, di=77.5mm,	1246787
	1	pcs	t=16mm, PCD=170mm, n=4x, 18mm, St st AISI 316L (1.4404)	1
012	1034549		S.C. Flange: Sanitary discharge blind, PN10, OD=210mm, t=16mm,	1069873
	1	pcs	PCD=170mm, n=4x, 18mm, St st AISI 316L (1.4404), DN40-DN100, With	1
013	1011972		S.C. Flange: Dirty oil/bilge water discharge, DN40, PN10, OD=215mm,	1247276
	2	pcs	di=49.6mm, t=20mm, PCD=183mm, n=6x, 22mm, St st AISI 316L (1.4404)	1
014	1034474		S.C. Flange: Dirty oil/bilge water discharge blind, PN10, OD=215mm,	1068662
	2	pcs	t=20mm, PCD=183mm, n=6x, 22mm, St st AISI 316L (1.4404), DN40-DN1	1
017	1000803		Plug valve, Self-closing, 724, 1.1/2" (40), BSPP female, Lever with	1066710
	6	pcs	weight, PN2.5, Right closing, Bronze RG5	1
018	1005922		ASSY, Flush Sounding Plug, G 1 1/2inch, dowel with plug, bronze plug	1899688
	9	pcs	with int. hex. 24, with copper ring, St st AISI 316L (1.4404), a	1
019	1000275		Check valve wafer type, 2624, Disc, DN65, Sealing: Metal, PN16,	
	2	pcs	Spring, Bronze CuSn12-C, EN 558-1	

BUREAU VERITAS
Stamped document, refer to 1st page

TransNo: TE-513233-00012-01 / Issue: For Approval / Date: 22-01-2024