



Industrieterrein Avelingen West 20  
4202 MS GorinchemP.O. Box 1  
4200 AA Gorinchem

The Netherlands

phone +31 (0) 183 63 99 11  
fax +31 (0) 183 63 21 89info@damen.com  
www.damen.comBILL OF  
MATERIAL

Lubrication oil system				Top Part	M360
Project No.	513233	Function	360	Drawn	NCO
Yard No.	Section/Compartment			Check	CPAD01
COPYRIGHT DAMEN SHIPYARDS GROUP				Document number	5497697
				Date	09-11-2023
				Sheet	1
				Revision	A01

POS	PART		DESCRIPTION	DOC NO	
	QT.	UNITS		SHT	
001	1399625		[TA], Pump, Electrical, BT-HM-32D4, 50Hz/1.1kW/400V/1450rpm,		
	2	pcs	60Hz/1.3kW/440V/1750rpm, G1.1/2", G1", Cast iron GGG 40 (EN-JS 10		
003	1204252		Pressure gauge, Bourdon tube, 3660, -1/0.6bar, D=63mm, 1/4",	2188438	
	2	pcs	BSPP male, Mount:Direct, Conn:Below, Liquid-damped, Case:Stainles	1	
004	1155843		Pressure gauge, Bourdon tube, 3660, 0/6bar, D=63mm, 1/4", BSPP male,	2188438	
	2	pcs	Mount:Direct, Conn:Below, Liquid-damped, Case:Stainless steel, Co	1	
005	1000358		Pressure gauge valve, 861, 1/4" (8), BSPP male, BSPP female,	1062556	
	4	pcs	Hand wheel, PN125, Brass	1	
006	1011347		Y-filter, 1019, DN40, PN16, Flange, FL:PN16, Mesh=1mm, With drainage	1324894	
	1	pcs	conn., Cast iron GG 25 (EN-JL 1040)	1	
007	1000449		Globe valve, 241, Straight, Fixed disc, DN25, Flange, Hand wheel,	1063480	
	2	pcs	PN16, FL:PN16, Cast iron GG 25 (EN-JL 1040), EN 558-1	1	
008	1000520		Globe valve, 242, Right-angled, Fixed disc, DN40, Flange, Hand wheel,	1154112	
	2	pcs	PN16, FL:PN16, Cast iron GG 25 (EN-JL 1040), EN 558-1	1	
009	1000705		Globe valve, 242, Right-angled, SDNR disc, DN25, Flange, Hand wheel,	1154112	
	2	pcs	PN16, FL:PN16, Cast iron GG 25 (EN-JL 1040), EN 558-1	1	
010	1002618		Single bulkhead flange, PN10, OD=115mm, t=30mm, PCD=92mm, n=4x, M12,	1055924	
	1	pcs	Steel S235JR (1.0038)	1	
011	1011316		Driptray, 250x250x150 with drain, For drain points in lub. oil	1233684	
	1	pcs	system, Steel S235JR (1.0038)	1	
012	1011066		Check valve, 505BR, Swing type, Straight, 1" (25), BSPP female,	1062920	
	2	pcs	Sealing:Bronze, PN16, Bronze RG5	1	
013	1012165		Ball valve, 1607, Straight, 1" (25), BSPP female, Sealing:PTFE,	1060923	
	2	pcs	Lever, PN50, Brass CuZn40Pb2, Nickel-plated	1	
014	1006959		Hose saddle, W=312mm, Depth=150mm, Wall mounting, Steel Grade A	1032858	
	2	pcs		1	
015	1012176		[TA], Hose, Oil, 310-16, Dint=1 inch L= 10m, 2xouter thread 1inch,		
	2	pcs	Rubber		
016	1012333		Quick release coupling, Valve/thread, Coupling (female), BSPP female,	1089259	
	2	pcs	1" (25), With valve, Self-venting, Dust cap, Steel	1	
017	1012334		Quick release coupling, Valve/thread, Plug (male), BSPP female,	1089259	
	4	pcs	1" (25), With valve, Self-venting, Dust cap, Steel	1	
018	1011093		[TA], Level Switch, A01041 FL-SQR Besta, FLANGE 92x92, max 300	1102581	
	1	pcs	deg.C, IP65, cable connection M20 x 1.5, Stainless steel	1	
019	1554712		Pump Manual Driven, Semi Rotary, fig 950, size K-2, connection 1		
	1	pcs	inch, D=170, Cast iron		

TransNo: TE-513233-00012-01 / Issue: For Approval / Date: 22-01-2024